

Zubehör für Thermoelemente

— Anschlüsse —

■ Watertight connections

This stainless steel compression fitting allows watertight connection of a temperature sensor using a stainless steel not adjustable ferrule or a teflon adjustable ferrule.



• Technical features

Working temperature :

Stainless steel ferrule (316L) from -50°C to +400°C (**Not adjustable**)
 Teflon ferrule (PTFE) from -50°C to +250°C (**Adjustable**)



• Part numbers

Probe Ø (mm)	Cylindrical gas	Stainless steel ferrule	Teflon ferrule
3	1/8"	RCI-3/18	RCT-3/18
3	1/4"	RCI-3/14	RCT-3/14
4	1/8"	RCI-4/18	RCT-4/18
4	1/4"	RCI-4/14	RCT-4/14
4	3/8"	RCI-4/38	RCT-4/38
6	1/8"	RCI-6/18	RCT-6/18
6	1/4"	RCI-6/14	RCT-6/14
6	3/8"	RCI-6/38	RCT-6/38
6	1/2"	RCI-6/12	RCT-6/12
8	1/4"	RCI-8/14	RCT-8/14
8	1/2"	RCI-8/12	RCT-8/12
10	1/2"	RCI-10/12	RCT-10/12
12	1/2"	RCI-12/12	RCT-12/12
14	1/2"	-	RCT-14/12

